



Tile & Grout Caulk

- ✓ 100% Acrylic
- ✓ Silicized
- ✓ Moisture & Mildew Resistant



NET 10.3 Fl. Oz. (310 ml)



IMPORTANT!

This product contains colorants that may stain some porous materials such as walls, wallpaper, etc. Mask or shield these areas to protect from staining. Test in a non-conspicuous area to see if staining will occur.

DIRECTIONS

1. Surfaces must be clean and free of dust, dirt, oil and other foreign substances.
2. Cut spout to desired bead thickness.
3. Remove all old caulking before applying new caulk. Apply when temperature is above 40° F.
4. Tool caulking within 20 minutes of application. Use wet finger or wet smooth sponge.
5. Excess may be cleaned up with a damp cloth before caulk fully cures.

NOTICE TO PURCHASER

Manufacturers liability for damages hereunder shall not exceed the purchase price of the goods used. Manufacturer warrants only that the goods will be free from defects in material. The foregoing warranty is in lieu of all other warranties, express or implied, including those of merchantability or fitness for any other purpose not expressly set forth herein. No liability is assumed by manufacturer except as expressly stated herein. In no event shall manufacturer be responsible for incidental or consequential damages arising out of or in connection with the use of this product by user, buyer's user, or any other person.

KEEP OUT OF REACH OF CHILDREN

Don't forget about our MUST HAVE
Caulk Installation Tools available on our site.

COLOR FAST INDUSTRIES, INC.
COLTON, CA 92324
WWW.COLORFASTIND.COM

