



TECHNICAL BULLETIN

DURA SEAL® RENOVATOR

DURA SEAL® Renovator Cleaner and Reconditioner is a special balance of solvent and resin that cleans and reseals hardwood floors previously finished with **DURA SEAL® Penetrating Gym Finish**, **DURA SEAL® Penetrating Finish** or **DURA SEAL® Dura Finish® Liquid Floor Wax**. **DURA SEAL Renovator™** Cleaner and Reconditioner can also be used on terrazzo, concrete or unglazed terra cotta tile.

WARNING! Removal of old paint by sanding, scraping, or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

DIRECTIONS:

1. Using a brush or lambswool applicator, apply a coat of **DURA SEAL Renovator Cleaner and Reconditioner** at a coverage rate of 900 square feet per gallon to an area of approximately 100 square feet.
2. Allow 5 minutes for **DURA SEAL Renovator Cleaner and Reconditioner** to act before removing excess with steel wool.
3. Scrub floor with #3 steel wool until **DURA SEAL Renovator Cleaner and Reconditioner** and dirt have been removed from the floor and the surface is dry to the touch. NOTE: Periodic changing of the steel wool is essential to ensure proper removal of dirt and **DURA SEAL Renovator Cleaner and Reconditioner**.
4. Allow product to dry at least 4 hours. NOTE: Drying time will be increased by high humidity, low temperature or inadequate removal of excess material.
5. If desired, apply a finish coat of **DURA SEAL Penetrating Finish** or **DURA SEAL® Paste Wax**.

NOTE: **DURA SEAL Renovator Cleaner and Reconditioner** is neutral in color. For colored floors mix 4 parts **DURA SEAL Renovator Cleaner and Reconditioner** with one part **DURA SEAL Penetrating Finish** color of your choice.

DURA SEAL Renovator Cleaner and Reconditioner does not require a finish coat.

DRYING TIME: Approximately 4 hours. **NOTE:** Drying time will be increased by high humidity, low temperature, lack of air movement or inadequate removal of excess material.

CLEAN UP: Clean equipment with paint thinner, turpentine or mineral spirits.

COVERAGE: 900 square feet per gallon

SOLVENT: Non-photochemically reactive

CAUTION: COMBUSTIBLE MIXTURE N.Y.F.D. C. OF A. NO.1187

KEEP OUT OF REACH OF CHILDREN.

DANGER: Contains Petroleum Distillates, Dipropylene Glycol Methyl Ether and Diacetone Alcohol. Eye and skin irritant. Avoid contact with eyes and skin. Wear safety glasses and rubber gloves when handling. Harmful if swallowed. Do not take internally. Avoid inhalation and use only with adequate ventilation. If adequate ventilation cannot be maintained, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Do not use or store near heat, sparks, flame or other sources of ignition. Close container after each use.

FIRST AID: If swallowed, do NOT induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, immediately flush eyes thoroughly with water, then remove any contact lenses. Continue to flush eyes with water for at least 15 minutes. If irritation persists, get medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention. If affected by inhalation, immediately remove to fresh air. If symptoms persist, CALL PHYSICIAN.

SIZE	SKU #	CASE/PACK
Gal	81700	6

07/24/07