



MATERIAL SAFETY DATA SHEET

Fusion Pro - Single Component Grout

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Fusion Pro - Single Component Grout
Product Use: Grout.
Manufacturer/Supplier: Custom Building Products
13001 Seal Beach Blvd
Seal Beach, CA
90740
Phone Number: (562) 598-8808
Emergency Phone: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500
Date of Preparation: May 17, 2011 **Revision Date:** April 16, 2012

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Medical Conditions Aggravated By Exposure: Because of its irritating properties, dust may aggravate preexisting skin, eye, and respiratory conditions.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Ethanol	64-17-5	0.5 - 1.5
Ethylene glycol	107-21-1	0.5 - 1.5
Titanium dioxide	13463-67-7	0.5 - 1.5
Silica, crystalline, quartz	14808-60-7	60 - 100



MATERIAL SAFETY DATA SHEET

Fusion Pro - Single Component Grout

Section 4: FIRST AID MEASURES

- Eye Contact:** In case of contact, immediately flush eyes with plenty of water. If easy to do, remove contact lenses, if worn.
- Skin Contact:** In case of contact, immediately flush skin with plenty of soap and water. Call a physician if irritation develops or persists.
- Inhalation:** If breathed in, move person into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).
- Note to Physicians:** Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

- Flammability:** Not flammable by WHMIS/OSHA criteria.
- Means of Extinction:**
- Suitable Extinguishing Media:** Powder, water spray, foam, carbon dioxide.
 - Unsuitable Extinguishing Media:** Not available.
- Products of Combustion:** May include, and are not limited to: oxides of carbon.
- Explosion Data:**
- Sensitivity to Mechanical Impact:** Not available.
 - Sensitivity to Static Discharge:** Not available.
- Protection of Firefighters:** Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
- Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
- Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for Clean-Up:** Scoop up material and place in a disposal container. Provide ventilation.
- Other Information:** Not available.

Section 7: HANDLING AND STORAGE

- Handling:** Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.



MATERIAL SAFETY DATA SHEET

Fusion Pro - Single Component Grout

Storage:

Keep out of the reach of children. Keep container tightly closed. Do not store at temperatures above 49 °C / 120 °F.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Ethanol	1000 ppm	1000 ppm
Ethylene glycol	Not available.	50 ppm
Titanium dioxide	15 mg/m ³ (total dust) ((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)); ((30 mg/m ³)/(%SiO ₂ +2) TWA (total));	10 mg/m ³
Silica, crystalline, quartz	((250)/(%SiO ₂ +5) mppcf TWA (resp))	0.025 mg/m ³

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Not available.
Color:	Not available.
Odour:	Not available.
Odour Threshold:	Not available.
Physical State:	Solid.
pH:	9.0 -9.5
Viscosity:	800K - 1 million cPs @ 24°C (75°F)
Freezing Point:	Not available.
Boiling Point:	Not available.
Flash Point:	Aqueous suspension, not measured.
Evaporation Rate:	Not available.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Specific Gravity:	1.82 - 1.88 @ 24°C (75°F)
Solubility in Water:	Miscible.



MATERIAL SAFETY DATA SHEET

Fusion Pro - Single Component Grout

Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	10 - 12%
VOC content, wt. g/L:	54 g/L

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: None known.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient	LD₅₀ (oral)	LC₅₀
Ethanol	7060 mg/kg, rat	20000 ppm 10hr, rat
Ethylene glycol	4000 mg/kg, rat	> 200 mg/m ³ 4hr, rat
Titanium dioxide	>10000 mg/kg, rat	Not available.
Silica, crystalline, quartz	120 g/kg, rat (TD ₀₁)	Not available.

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Hazardous by WHMIS/OSHA criteria.

Carcinogenicity: Hazardous by WHMIS/OSHA criteria.

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen *
Ethanol	G-A3, I-1
Ethylene glycol	G-A4
Titanium dioxide	G-A4, I-2B
Silica, crystalline, quartz	G-A2, I-1, N-1, CP65

* See Section 15 for more information.

Mutagenicity: Hazardous by WHMIS/OSHA criteria.

Reproductive Effects: Not hazardous by WHMIS/OSHA criteria.

Developmental Effects:

Teratogenicity: Hazardous by WHMIS/OSHA criteria.

Embryotoxicity: Hazardous by WHMIS/OSHA criteria.



MATERIAL SAFETY DATA SHEET

Fusion Pro - Single Component Grout

Respiratory Sensitization: Not hazardous by WHMIS/OSHA criteria.

Skin Sensitization: Not hazardous by WHMIS/OSHA criteria.

Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Ground Classification

Not regulated

TDG Ground Classification

Not regulated

IATA Classification

Not regulated

IMDG Classification

Not regulated

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Ethanol	Not listed.	Not listed.	Not listed.	Not listed.
Ethylene glycol	Not listed.	Not listed.	5,000	313
Titanium dioxide	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

New Jersey Right-To-Know: Silica Quartz, Ethyl alcohol, Titanium dioxide, 2-Butoxyethanol.

Pennsylvania Right-To-Know: Quartz, Ethanol, Titanium oxide, 1,2-Ethandiol. **Massachusetts**

Right-To-Know: Quartz, Ethyl alcohol, Titanium dioxide.



MATERIAL SAFETY DATA SHEET

Fusion Pro - Single Component Grout

California Proposition 65:

This product contains chemicals known to the State of California to cause cancer. (Silica crystalline, Titanium dioxide, Ethyl acrylate, N-Methylolacrylamide, Acrylamide, Acetaldehyde, 1,4-Dioxane, Ethylene oxide)

This product contains a known to the State of California to cause birth defects or other reproductive harm. (Ethylene oxide)

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Ethanol	DSL	Yes.
Ethylene glycol	DSL	Yes.
Titanium dioxide	DSL	Yes.
Silica, crystalline, quartz	DSL	Yes.

All ingredients are on DSL/NDSL and TSCA inventories or are exempt from listing.

HMIS - Hazardous Materials Identification System

Health - 1* Flammability - 0 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 1 Fire - 0 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

- Class D2A - Carcinogenicity
- Class D2A - Teratogenicity and Embryotoxicity
- Class D2A - Mutagenicity
- Class D2A - Chronic Toxic Effects
- Class D2B - Eye Irritant

WHMIS Hazard Symbols:



SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.



MATERIAL SAFETY DATA SHEET

Fusion Pro - Single Component Grout

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: February 24, 2015

Version #: 2.3

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com