Johnsonite[®]

POWER TAPETM ADHESIVE

M A T E R I A L S A F E T Y D A T A S H E E T

SECTION 1. PROPRIETARY PRODUCT IDENTIFICATION/MANUFACTURER

1.1 Proprietary Product Name: Power tape adhesive

1.2 Chemical Family: Acrylate Adhesive

1.3 Chemical name and Synonyms: Modified Polyacrylate traction glue

1.4 Molecular formular: Organic Materials

1.5 Manufacturer:

Johnsonite

16910 Munn Road

Chagrin Falls, Ohio 44023

Phone: (800) 899-8916

(440) 543-8916

Fax: (440) 543-8920

24 hour Emergency Telephone: 864-967-7691

SECTION 2. HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS

Chemical CAS % by ACGIH OSHA
Name Number Weight TLV PEL

Ingredients: Non-hazardous

SECTION 3. HAZARDS IDENTIFICATION

Effects of over exposure: No hazards exist under normal handling conditions. Persons with extremely sensitive skin may be subject to dermatitis.

Carcinogen city data: Dermatitis may occur in persons with extremely sensitive skin.

EYE CONTACT: May cause slight irritation.

Reproduction effects: None known.

Mutagenicity data: None known.

Teratogenicity data: None known.

SECTION 4. FIRST AID MEASURES

Eye Contact: Flush with water for 15 minutes. Contact a physician if irritation

occurs.

Skin Contact: Wash with soap and water.

Emergency and First Procedures: Wash skin with soap and water, seek medical attention.

Ingestion: Induce vomiting, contact a physician.

SECTION 5. FIRE-FIGHTING MEASURES

Flash Point: (200°F): None

Extinguishing Method: Water foam, dry chemical.

Special Fire Fighting procedure: None **Unusual Fire and Explosion Hazard**: None

SECTION 6. ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is released or spilled: N/A

SECTION 7. HANDLING AND STORAGE

Handling: Use good hygienic practices. (Wash hands before eating, using washroom,

or smoking.) Keep out of reach of children.

Storage: Store above 40° F. Store in well ventilated area.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT:

Eye Face Protection: Wear splash goggles if contact with material is likely.

Skin Protection: Wear gloves if contact with material is likely.

Respiratory protection: Not normally required with good ventilation.

Engineering Controls: Normal room ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°F): Heat resistant to + 130 C degrees

Specific Gravity (Water = 1): N/A Vapor Pressure: Same as water. Vapor Density: (AIR = 1): N/A

Vapor Pressure (mm of Mercury): N/A

% Volatile by Weight: None

Appearance and Odor: Light brown silicon release paper covering glue with Polyester scrim, odor

free.

Percent Volatile: None

SECTION 10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable.
POLYMERIZATION: Will not occur.
CONDITIONS TO AVOID: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: None

SECTION 11. TOXICOLOGICAL INFORMATION

This product has been tested for toxicity (acute inhalation; acute dermal; skin irritation; oral) and has been found to be non-toxic as defined by The Federal Hazardous Substance Act, 16 CFR 1500.3.

SECTION 12. ECOLOGICAL INFORMATION

No information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposed of in accordance with federal, state, and local regulations.

SECTION 14. TRANSPORT INFORMATION

For domestic transportation purpose, this product is not designated as a hazardous material by the U.S. Department of Transportation.

SECTION 15. REGULATORY INFORMATION

TSCA: All ingredients are listed. SARA TITLE III:

Section 311 and 312 Health and Physical Hazards:

Immediate Delayed Fire Pressure Reactivity [X] [] [] []

SECTION 16. OTHER INFORMATION

HMIS RATINGS: Health = 1 Flammability = 1 Reactivity = 0
Personal Protective Equipment = B

(Hazard Rating Scale: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe)

Johnsonite believes the statements, technical information, and recommendations contained herein are reliable. They are given without any warranty or guarantee of any kind, expressed or implied.