

960 Cove Base Adhesive

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Johnsonite #960 Acrylic Cove Base Adhesive specifically formulated for installing Johnsonite Rubber and Vinyl Wall Base, Millwork Wall Base, Tightlock and Perceptions Wall Base and Vent Cove Base.

1.2. Manufacturer:

Johnsonite, Inc.,	Phone:	(800) 899-8916
16910 Munn Road		(440) 543-8916
Chagrin Falls, Ohio 44023	Tech:	Ext 9297
Web: www.johnsonite.com	Samples:	Ext 9299
E-mail: info@johnsonite.com	Fax:	(440) 632-8920

1.3. Proprietary Product Description

- Johnsonite #960 Cove Base Adhesive is a nonflammable, solvent free, acrylic water-base adhesive.
- For installations over dry porous interior wall surfaces.
- Contains no hazardous or carcinogenic ingredients as defined by OSHA chemicals and meets all federal, state and local air quality regulations.
- Contributes to LEED Certification (E.Q. 4.1: Low-Emitting Materials: Adhesives and Sealants).
SCAQMD Rule 1168 – VOC compliant
SCAQMD Rule 443.1 –
Less than 1 gram VOC per liter of materials
Less than 1 gram VOC per liter of coating

2. PRODUCT PERFORMANCE and TECHNICAL DATA:

- Base – Acrylic Polymer
- Color – Light Tan Paste
- Shelf Life – 1 year at 70°F (21°C) when stored in unopened, original container in a dry area.
- Freeze thaw up to 5 cycles at 20°F (-6.7°C)

2.1. Application:

Porous Wall:

Coverage	2.5"	300-350 lin. ft./gal.
	4"	200-250 lin. ft./gal.
	6"	100-150 lin. ft./gal.
	30 oz. cartage	62 to 75 lin. ft.

Non-Porous Wall use Johnsonite #946 Contact Bond

3. INSTALLATION

3.1. General Installation Requirements:

- Johnsonite flooring and adhesives must be site conditioned at room temperature for a minimum of 48 hours prior to, during, and after installation. Room temperature must be maintained between 65° and 85°F (18° and 30°C) with HVAC system operating. A minimum temperature of 55°F (13°C) must be maintained afterwards. The ambient relative humidity should be between 40% and 60%.

- Wall shall be smooth, flat, permanently dry, clean and free of all foreign material such as dust, paint, grease, oils, solvents, sealers, and old adhesive residue.
- Do not install on exterior surfaces subject to weather.

4. AVAILABILITY and COST

For availability and cost contact authorized Johnsonite distributors nationwide.

5. LIMITED 1 YEAR WARRANTY

For complete details, contact Johnsonite or an authorized Johnsonite distributor.

6. Traffic:

- Wait 72 hours after installation before performing initial cleaning
- A regular maintenance program must be started after the initial cleaning.

7. TECHNICAL SERVICES

For current Installation and Maintenance Instructions, Product Specifications, Material Safety Data Sheet and other technical data, visit us on the web at www.johnsonite.com or contact Johnsonite at (800) 899-8916.



covebase-n-transitions.com