

CARPET SHIELD®

Product Information

Application

Warranty

Before using, the purchaser and/or user must determine suitability of this product for the intended use and the purchaser and/or user assumes all risks and liabilities in connection therewith.

Because there are so many variations in carpet fibers and products used to prevent carpets from staining, it is imperative that the user of this product determine suitability. To determine suitability test Carpet Shield on a small portion of carpet that is in a non-exposed area. Leave Carpet Shield in place for at least 48 hours and then inspect to insure there was no disturbance to the carpet fibers.

Before applying Carpet Shield please carefully read the following important information:

**C
A
U
T
I
O
N**

- Carpet Shield is for carpeted surfaces only, do not apply to any other surface or allow Carpet Shield to overlap beyond the carpeted area or onto hard surfaces like wood or tile
- Use only on completely dry carpeting. If carpeting was recently cleaned allow at least **24 hours** for carpeting to dry and cleaning agents to dissipate
- For any newly installed carpeting do not use Carpet Shield for **72 hours** to allow adhesive vapors to dissipate completely through the padding and the carpet
- If subjected to extreme conditions of high temperature, direct sunlight, heavy foot traffic or outdoor exposure, it is recommended that the Carpet Shield film be inspected and replaced with new material more frequently
- Do not use in extreme humidity conditions or high moisture areas like basements
- Use on synthetic fibers only. **Not** for use on oriental carpets
- Carpet Shield is for **temporary protection up to 45 days, REMOVE ON 45TH DAY** or sooner
- If Carpet Shield is exposed to temperatures over 95°F, direct sunlight or outdoor exposure, product should be inspected and replaced weekly

Easy Application Steps for Carpet Shield

Remove over wrap from the product and locate the start of the film. Pull film off the roll slightly to determine the direction the film unwinds. Place film sticky side down on the carpeting, secure start of the roll by applying slight pressure and then push roll in the desired direction. Apply slight pressure over the top of the film as you roll out to the desired length and then cut with a utility knife or sharp edge. To remove simply lift film up at an edge and pull off.

Product Storage Guidelines

For best performance store at room temperature and out of direct sunlight exposure. If Carpet Shield is stored in extreme conditions (over 95°F or below 40°F) allow product to return to room temperature prior to use.

Limited Warranty

Before using, the purchaser and/or user must determine suitability of this product for the intended use and the purchaser and/or user assumes all risks and liabilities in connection therewith. The sole obligation of the manufacturer, distributor, and/or seller of this product shall be replacement of the Carpet Shield product if notified of the defect within six months of the date of purchase. Such quantity of the product deemed defective shall be replaced or the amount of the purchase refunded and there shall be no liability to injury, loss or damages, either direct or consequential, arising out of the use or inability to use this product. The company disclaims all oral warranties of any kind. This limited warranty offered in connection with the manufacture and sale of the product is exclusive and in lieu of any warranties expressed, implied, or statutory, including without limitation any direct or implied warranty of merchantability or fitness for a particular use. **In the event of a claim, failure to notify manufacturer of incident prior to any remedy, not limited to cleaning of carpeting or carpet replacement, voids any liability on the part of the manufacturer.**

Rugrats Flooring INC cannot be held liable by purchasers / users who do not read and comply with these instructions from the manufacturer.